

Environmentally friendly



---

## TECHNICAL REQUIREMENTS ROTARY CUT VENEER FOR PARQUET

**Manufacturer:**            **Wotan Forest, a.s.**                            **division of flat material**  
Rudolfovská tř. 202/88                            Kvasinská 297  
370 01 České Budějovice                            517 01 Solnice  
Czech Republic    Czech Republic  
Web: [www.wotanforest.cz](http://www.wotanforest.cz)

1. Product: **ALFA floor** - veneer for parquet
    - 1.1 Product identification – spruce rotary cut veneer for three-layer parquet production
    - 1.2 Veneer method:
      - Wood species - spruce
      - Cut to size veneer – veneer sheets should be prepared in such way that sides are parallel, edges sharp and all angles right. Every sheet must be rectangle shape, trapezium is not acceptable.
      - Veneer sheets must be clean, sawdust, oil stains, waterlogged stains are not acceptable on the surface
      - Veneer must be packaged on a pallet, top and bottom covered with plywood board, wrapped with stretch foil.
    - 1.3 Quality control  
Go through constant quality securing process in all stages of the production
  2. Dimension:
    - Thickness – 2 mm (- 0,2 + 0,2 mm)
    - Width – from 200 mm until 1250 mm (-0 + 10 mm)
    - Length - from 1700 mm until 2500 mm (-0 + 10 mm)
-

Environmentally friendly

3. Quality characteristics:

<b>ALFA floor – veneer for parquet</b>		
<b>Wood defects</b>	longitudinal cracks, open splits	allowed up to 10 mm width and 1/4 length veneer sheet, max.1 pcs from every side
	closed cracks close splits	allowed up to 1/3 length veneer sheet, max. 1 pcs from every side
	rot	not allowed
	blue stain	allowed up to 5% veneer sheet
	brown sap pocket	allowed up to 150 mm <sup>2</sup>
	mould	not allowed
	resin pocket	allowed up to 150 mm <sup>2</sup>
	mechanical damages	not allowed
	insect damages	not allowed
	sound knots	allowed
	dead knots, unsound knots	allowed up to Ø 20 mm
	open knots, knots holes	allowed up to Ø 30 mm
	wave	allowed up to hight 50 mm
	humidity	4 – 6 % 5 – 7 %

Product – ALFA floor veneer for parquet corresponds to the quality characteristics. This is issued under the sole responsibility of the manufacturer.

Solnice 1.11.2020

creator Ing. Josef Kopecký  
quality engineer

for manufacturer Ing. Michal Polák  
COO division of flat material